

Performance Curve for Metering Pump


DATE	
CUSTOMER	
ITEM NO.	
PUMP MODEL	JMH7000

PUMP SPECIFICATIONS

MAX. CAPACITY		MAX. DIS. PRESSURE	STROKE RATE	CONNECTION	
60 Hz	7,000 cc/min.	10 kgf/cm ²	114 spm	Suction	KS 10K 20A FF
50 Hz	5,800 cc/min.		95 spm	Discharge	KS 10K 20A FF

MOTOR SPECIFICATIONS

PHASE	FREQ.	VOLTAGE	POLES	OUTPUT	RATED CURRENT	INS. CLASS	PROT'N GRADE
3	60Hz	220/380V	4	0.75kW	3.3/1.9A	F	IP55
MAKER		SIEMENS		TEST CONDITION		FOR WATER 20°C & 1.0S.G.	



PREPARED BY	CHECKED BY	APPROVED BY	REV. No.	REVISED BY	CHECKED BY	APPROVED BY
<i>W. PARK</i>	<i>W. PARK</i>	<i>S. C. KIM</i>				



E-WHA CHEMICAL FEEDER CO., LTD.

주식회사 이화정량펌프

26-6, Seoneup-ri, Janghownon-eup, Icheon-City, Kyung Ki-Do, Korea 467-904

Tel. +82-31-642-8000

Fax. +82-31-642-4071

E-mail : ewhapump@ewhapump.com

URL <http://www.ewhapump.com>